It is our commitment to provide the service with the highest standard of safety, quality and reliability that meet the specified requirements and expectations.



**8 Million Pixels** Traffic Camera Video **Vehicle Detector** iTraffiCam

Road vehicle detection | Video Transmission | Queue Detection



iTraffiCam is an

video integrated traffic information collection device suitable for outdoor environments. It collects traffic detects traffic vehicles, and optimizes traffic signal control systems in highways, tunnels, urban intersections and sections.

### Easily solve the following problems

 Choose wireless traffic camera detector to avoid clutter.



The truck's chassis is high, so it can't be sensed.



 Cutting the ground coil troublesome, time-cinsuming and laborious.



 Causes the driver feel and angry irritable, and the time for work is reduced, resulting in economic loss for driver and the region.







### iTraffiCam

### **Eight Advantages**

















**Multiple Function and Good Practical** 

# KEY FUNCTIONAL

· Road vehicle detection





License Plate Registration (LPR)










### QUALITY POLICY

It is our commitment to provide the service with the highest standard of safety, quality and reliability that meet the specified requirements and expectations.












## iTraffiCam

iTraffiCam CAMERA



iTraffiCam CONTROLLER



CAMERA EXTERNAL VIEW

### **iTraffiCam - CAMERA SPECIFICATION**

	Detection Functionalist	Vehicle presences + data + video
	Detection Zones	8
	Detection Outputs	80.5
-	Resolution	1920x1080 30fps
	Frame rate	20 FPS
	Mounting Height	3,5 - 12M
	Compression	MJEP, H.265
	Detection Distance	Wide Angle 2.8mm 0-30m. Narrow Angle 6.00mm 15-75
	Communication PC - Sensor	Interface & Via Ethernet
	PC tool for setup	Traffic Configuration Tool
	EMC	Electromagnetic Compatibility 2004/108/EG
	Protection grade	Housing IP66
	Dimension	80Hx100Wx245D
	Operating volatage	12-42

### **iTraffiCam - CONTROLLER SPECIFICATION**

Flash	Flash 8GB, SD Card
Memory	DDR3 1GB
Image Sensor	8MP
Night Vision	Yes
Reset	H/W, Software Reset
Video Input	1 Channel IP Camera
Connectors	10/100 Fast Ethernet
Power	DC12V 1A, Max 12W
Adaptor	DC12V 2A
POE	Yes
Dimension	172 x 88 x 24.5mm
Weight	530g
Operating Condition	Temp.: 0 ~ 60°C Humidity.: 5~95% RH non-condensing
Certification	CE/FCC
Support Res.	VGA ~ Full HD (1080p)



### CONTACT

TEL NO.: 09-5315333



MOBILE NO.: 019-2589137



EMAIL: info@kaf2u.com



WEBSITE: www.kaf2u.com

#### Disclaimer

ned proprietary to KAP idea tech. Do not copy this document without express permission from authorized KAF smployee. Do not distribute this document without the express approval of KAF director. Unauthorized use, reproduction or distribution. This profile includes data that shall be disclosed and shall not be duplicated, used, or disclosed - in whole or in part - for any purpose KAF further requests the cooperation of client in maintaining strict confidentiality of all the proprietary information contained in this Profile on the basis that it contains information on

### **ADDRESS**

NO.102, JALAN BUKIT UBI 25200 KUANTAN, PAHANG DARUL MAKMUR